



- 1 - CONTACT MATERIAL: CARBON STEEL, 304 ST. ST. OR 316 ST. ST.
- 2 - D.C. MOTOR, 1/3 HP, 90 VA, BALDOR OR EQUAL.
- 3 - SPEED REDUCER: OHIO GEAR, MODEL, 2175, 60:1 RATIO OR EQUAL.
- 4 - BIN VIBRATOR, 1/4 HP, 460/3/60, 1800 RPM, TENN.

DO NOT SCALE PRINT UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES : XX = ±.01 FRACTIONS XX = ±.005 ANGULAR = ±1/2°		REMOVE ALL BARRS DIMENSIONS .005-.015 ALL SMALL FILETS .020-.040R 63-125 MICRO INCHES	
1 REV. 1 DESCRIPTION BELT FEEDER BF-75 WITH 7" WIDE BELT & 5 CU.FT. BIN	ULM 6/16/06	SCALE 1/8" = 1"	PART NO. C-47956

Vibra Screw Incorporated
 785 UNION BLVD.
 TORONTO, ONT. M2H 0Z612

THE REPUTATION OF THIS COMPANY ADOPTS NOT TO REPRO-
 DUCE, COPY, TRANSMIT OR USE THIS DOCUMENT IN WHOLE OR IN
 PART WITHOUT THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.