



**NOTES:**

1. CONTACT MATERIAL - CARBON STEEL, 304 SS, 316 SS.
2. GYRATOR MOTOR: 3 HP, 1750 RPM,TEFC, 230 OR 460/3/60.
3. AL ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
4. ALL CONNECTIONS TO BIN DISCHARGER MUST BE FLEXIBLE.

NEOPRENE COVERED CABLE  
(SO 14/4) APPROX. 6' LG.  
SUPPLIES BY V.S.

6K GYRATOR ASSY  
SEE NOTE 2 & 3

"A" OUTLET SIZE	"C" OVERALL HEIGHT
8"	43 3/8"
10"	42 3/8"
12"	41 3/8"
14"	40 3/8"

THIS DRAWING TO BE USED FOR REFERENCE ONLY

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

**Vibra Screw Incorporated**  
755 Union Blvd. Totowa, N.J. 07512-2207

TITLE: 6'-0" DIA. BIN DISCHARGER WITH PREASSEMBLED MOUNTING RING AND 6K GYRATOR

DWN/DATE: MJM 8/22/01  
CAD FILE NAME: N:\BA\BD\STDASSY\17979

DWG. NO. 17979-SD  
REV. NO. 1