


- NOTES:
- 1 - CONTACT MATERIAL: 304 STAINLESS STEEL.
  - 2 - GEAR MOTOR TO BE: 1/4 HP, 230-460/3/60.40.7 RPM.
  - 3 - VIBRATOR MOTOR, 1/2 HP, #VE3 18/900, 460/3/60.
  - 4 - ALL CONNECTIONS TO BE FLEXIBLE.
  - 5 - ALL CONNECTIONS TO TROUGH TO BE FLEXIBLE.

REV.	DESCRIPTION	DATE	CHK. BY	APP. BY
1	RELEASED FOR STANDARD	5/20/06		

DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES:	
XX = ±.01	
XX = ±.005	
FRACTIONAL = 1/32"	
ANGULAR = ±1/2°	
BREAK SHARP EDGES .005-.015	
ALL SMALL TILLETTS .020-.040K.	

 <b>Vibra Screw Incorporated</b> 10100A, N.J. 07912 795 UNION BLVD.	
TITLE	VIBRA BLENDER
SCALE	3/16"=1"
CAD FILE NAME	BLENDER V\18076
DWG. NO.	VB-C-18076
REV. NO.	1

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE OR TRANSMIT IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.